NSR Application A0001036 Bolt 5-2524H F026880 May 26, 2015

Air Quality Division Application for NSR Permit

NSR Application

Date application received: 05/26/2015

Is this a legacy NSR Application? No

This information should be filled out for each New Source Review (NSR) application. An NSR permit is required for all air contaminant sources (emissions units) installed or modified after January 1, 1974. See the application instructions for additional information.

Emission Unit application reason summary :	X Construction	Synthetic Minor
	Modification	Temporary Permit
	Reconstruction	Other

Facility Type : Sage Grouse :

Purpose of Application

Please summarize the reason this permit is being applied for.

to construct a new single well sweet crude oil and natural gas production facility known as the Bolt 5-2524H, located in the in the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of Section 25, T42N, R72W approximately twelve (12) miles south of Wright, in Campbell County, Wyoming.

Has the facility changed location or is it a new/greenfield facility? Yes
Has a Land Use Planning document been included in this application? No
Does production at this facility contain H2S? No

Federal Rules Applicability - Facility Level

Prevention of Significant Deterioration (PSD)

Not affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not affected

These rules are found under WAQSR Chapter 6, Section 13

13.

- Trade Secret Information - One or more Emissions Units in this application contains trade secret information.

_

Permit Application Contact - Newly created contacts and application contact changes will be saved when the application is saved.

Curtis Rice	Senior Environmental Specialist	EOG Resources, Inc.		
Name	Title	Company		
600 17th Street, Suite 1000N	Denver, CO	80202		
Street Address	City/Township, State	Zip Code		
(303)262-9946		Curtis_Rice@eogresources.com		
Phone	Fax	E-mail		

Modeling Section

Ambient Air Quality Impact Analysis: WAQSR Chapter 6, Section 2(c)(ii) requires that permit applicants demonstrate that a proposed facility will not prevent the attainment or maintenance of any ambient air quality standard.

Has the applicant contacted AQD to determine if modeling is required? ${\tt No}$

Is a modeling analysis part of this application? ${\tt No}$

Is the proposed project subject to Prevention of Significant Deterioration (PSD) $_{\rm No}$ requirements?

Application Attachments

Required Attachment	Public Document Id	Attachment Type	Description
х	5266	Process Flow Diagram	process flow-site diagram
х	5267	Emissions Calculations	emission calculations
х	5268	Cover Letter/Project Description	Cover letter and process description
х	5269	Equipment List	equipment list
х	5270	Facility Map	facility map

- Notes

User Name	Date	Note
O SCI Hallic	Duto	11010

AQD EU ID: DHY001

AQD EU description:

Company EU ID: DHY1

Company EU Description: 2.0 MMCFD TEG

Dehydration Unit w/reboiler

overheads

condenser, Kimray Model 4020 glycol circulation pump, and 0.75 MMBtu/hr reboiler heater

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Dehydration Unit

Temperature of Wet Gas (F): 83 Water Content of Dry Gas 7.00

(lbs H2O/MMscf):

Pressure of Wet Gas (psig): 653.00 Manufacturer Name of Glycol Kimray

Circulation Pump:

Source of Motive Gas for field gas

Pump:

Water Content of Wet Gas Model Name and Number of 4020

Glycol Circulation Pump: (lbs H2O/MMscf):

Flow Rate of Dry Gas 1.11 (MMscfd):

Type of Glycol Circulation Gas

Pump:

Pump Volume Ratio 0.08 Actual LEAN Glycol 0.6700

(acfm/gpm): Circulation Rate (gallons/minute):

Maximum LEAN Glycol 0.6700 Circulation Rate

(gallons/minute):

Additional Gas Stripping: No

Include Glycol Flash No Tank/Separator:

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

Manufacturer Data

- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Criteria Pollutants:

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	
Volatile organic compounds (VOC)	33.7	0		0.13	0.6	GRI GlyCalc
Lead (Pb)	0	0		0	0	
Total Hazardous Air Pollutants (HAPs)	13.8	0		0.05	0.2	GRI GlyCalc
Fluoride (F)	0	0		0	0	
Hydrogen Sulfide (H2S)	0	0		0	0	
Mercury (Hg)	0	0		0	0	
Total Reduced Sulfur (TRS)	0	0		0	0	
Sulfuric Acid Mist (SAM)	0	0		0	0	

Hazardous Air Pollutants (HAPs) and Toxic Air Contaminants:

Pollutant	Pollutant				Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant Pre-		Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

^{**} AQD Calculated - See 'Help' for more information.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Subject to subpart

Part 63 NESHAP Subpart

HH - Oil and Natural Gas Production Facilities

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

These rules are found under WAQSR Chapter 6, Section

Not Affected

Required Public Document Attachment Type Description	on .
--	------

AQD EU ID: FLR001

AQD EU description:

Company EU ID: FLA1

Company EU Description: Steffes Dual Tip

Flare

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

 ${\bf Emission\ Unit\ Type: Flare}$

Emergency Flare Only: No Ignition Device Type: Pilot
Btu Content (Btu/scf): 2,776.90 Smokeless Design: Yes

Assist Gas Utilized: No

Waste Gas Volume: 28,538.60 Units: scf/day

Installation Date: 03/01/2015

Continuously Monitored: Yes

Describe Continuous continuous pilot flame monitored through Cygnet

Monitoring:

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to Emit (PTE) (tons/yr)*	Basis for Determinatio n*
Emission	Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*		
Particulate emissions (PE/PM) (formerly	0	0		0	0	

particulate matter, PM)					
PM # 10 microns in diameter (PE/PM10)	0	0	0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0	
Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0.3	1.3	AP-42
Carbon monoxide (CO)	0	0	0.08	0.3	AP-42
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards		otential to Potential to	
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant		Efficiency	Standards		Potential to Potential to	
	Category	Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

- Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	iu		

AQD EU ID: FUG001

AQD EU description:

Company EU ID: FUG1

Company EU Description: process fugitives

 Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Fugitive

Type of Fugitive Emission: Fugitive Leaks at O&G

Equipment and Service Type	Number of Each Equipment Type	Leak Rate (ppm)	Percent VOC
Connector; Gas	359	10,000.00	39.700
Flange; Gas	63	10,000.00	39.700
Open Ended Line; Gas	1	10,000.00	39.700
Other; Gas	28	10,000.00	39.700
Valve; Gas	121	10,000.00	39.700
Connector; Light Oil	142	10,000.00	95.000
Flange; Light Oil	49	10,000.00	95.000
Pump; Light Oil	7	10,000.00	95.000
Valve; Light Oil	67	10,000.00	95.000
Connector; Water/Light Oil	73	10,000.00	95.000
Flange; Water/Light Oil	26	10,000.00	95.000
Pump; Water/Light Oil	2	10,000.00	95.000
Valve; Water/Light Oil	39	10,000.00	95.000

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc

- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Criteria Pollutants:

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	
Volatile organic compounds (VOC)	6.2	0		0	0	AP-42
Lead (Pb)	0	0		0	0	
Total Hazardous Air Pollutants (HAPs)	0.1	0		0	0	AP-42
Fluoride (F)	0	0		0	0	
Hydrogen Sulfide (H2S)	0	0		0	0	
Mercury (Hg)	0	0		0	0	
Total Reduced Sulfur (TRS)	0	0		0	0	
Sulfuric Acid Mist (SAM)	0	0		0	0	

Hazardous Air Pollutants (HAPs) and Toxic Air Contaminants:

ſ	Pollutant	Category Conf	Pre-	Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant Category	Pre- Controlled Potential Emissions	Efficiency Potential to Emit (PTE)*	Units*	Potential to Emit (PTE) (lbs/hr)*	Basis for Determinati on*
		(tons/yr)				

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? $_{\rm N\odot}$

^{**} AQD Calculated - See 'Help' for more information.

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards arè listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Not affected

Prevention of Significant Deterioration (PSD)

These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Non-Attainment New Source Review

These rules are found under WAQSR Chapter 6, Section 13.

Not Affected

Required F Attachment	Public Document Id	Attachment Type	Description
--------------------------	-----------------------	-----------------	-------------

AQD EU ID: HET001

AQD EU description:

Company EU ID: HET1

Company EU Description: Trace Line Heater

- 0.75 MMBtu/hr

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Heater/Chiller

Fuel Sulfur Content: 0.00 Units: ppm

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0.11	0.48	AP-42

Carbon monoxide (CO)	0	0	0.09	0.4	AP-42
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant Category		Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

ſ	Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards arè listed under 40 CFR 60 - Standards of Performance for New Stationary

Sources.

Not affected

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 61) National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

^{**} AQD Calculated - See 'Help' for more information.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

Required Public Document Attachment Type Id	Description
---	-------------

AQD EU ID: HET002

AQD EU description:

Company EU ID: HET2

Company EU Description: heater treater -

0.375 MMBtu/hr

- Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

- Emission Unit Type Specific Information

Emission Unit Type: Heater/Chiller

Fuel Sulfur Content: 0.00 Units: ppm

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0.055	0.24	AP-42

Carbon monoxide (CO)	0	0	0.046	0.2	AP-42
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-			Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

ſ	Pollutant	Pollutant	Pre-	Efficiency Standards		Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 61)
National Emissions Standards for Hazardous Air Pollutants
(NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl

chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

^{**} AQD Calculated - See 'Help' for more information.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

AQD EU ID: HET003

AQD EU description:

Company EU ID: HET3

Company EU Description: reboiler heater -

0.75 MMBtu/hr

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Heater/Chiller

Fuel Sulfur Content: 0.00 Units: ppm

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for	
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*	
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0		
PM # 10 microns in diameter (PE/PM10)	0	0		0	0		
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0		
Sulfur dioxide (SO2)	0	0		0	0		
Nitrogen oxides (NOx)	0	0		0.11	0.48	AP-42	

Carbon monoxide (CO)	0	0	0.09	0.4	AP-42
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

ſ	Pollutant	Pollutant	Pre-	Efficiency Standards		Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 61) National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

^{**} AQD Calculated - See 'Help' for more information.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

Required Publication Attachment	olic Document Id	Attachment Type	Description
---------------------------------	---------------------	-----------------	-------------

AQD EU ID: LUD001

AQD EU description:

Company EU ID: TLO1

Company EU Description: truck oil loading

from storage tanks

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Loading/Unloading/Dump

Maximum Hourly Throughput 3 Units: barrels/hr

Detailed Description of truck loading crude oil from four (4) oil storage tank, 63.2 Loading/Unloading/Dump bbl/day (2.63 bbl/hr)

Source

*Provide detailed calculations documenting the potential emissions and emission factors used to calculate emissions from this source.

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	Basis for Determinatio n*
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in	0	0		0	0	

diameter (PE/PM10)					
PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0	
Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	1.5	0	0	0	AP-42
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0.1	0	0	0	AP-42
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Г	Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

- Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

- Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 63)
National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Not affected

Non-Attainment New Source Review

These rules are found under WAQSR Chapter 6, Section

Not Affected

Required Po	Public Document Id	Attachment Type	Description
-------------	-----------------------	-----------------	-------------

AQD EU ID: PNE001

AQD EU description:

Company EU ID: PNE1

Company EU Description: three (3)

pneumatic pumps (tank combustor scrubber, VRT combustor scrubber, BTEX condenser) each pump has a gas consumption rate of 214 scf/hr for a total of 642

a total o

scf/hr

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Pneumatic Equipment

Motive Force: Field Gas

VOC Content (%): 39.700 HAP Content (%): 0.900

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant			Potential to			
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions	0	0		0	0	

(PE/PM) (formerly particulate matter, PM)					
PM # 10 microns in diameter (PE/PM10)	0	0	0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0	
Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	77.5	0	0.34	1.5	AP-42
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	1.8	0	0.008	0.04	AP-42
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-	Efficiency Standards		Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

ſ	Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

- Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Not affected

^{**} AQD Calculated - See 'Help' for more information.

Pollutants (NESHAP Part 61)National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) National Emission Standards for Hazardous Air Pollutants

Not affected

(NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section

Required P Attachment	Public Document Id	Attachment Type	Description
--------------------------	-----------------------	-----------------	-------------

AQD EU ID: PNE002

AQD EU description:

Company EU ID: PNE2

Company EU Description: two (2) Electric

Pumps (recycle and

trace pumps)

Source Installation or Modification Schedule - Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Pneumatic Equipment

Motive Force: Other

VOC Content (%): 0.000 HAP Content (%): 0.000

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- **GRICalc**
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to Potential to Basis		
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	

Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant			Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Po	llutant	Pollutant			Potential to Potential to Emit (PTE) Emit (PTE)			
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air **Pollutants (NESHAP Part 63)**

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Not Affected

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section

Required Public Document Id	Attachment Type	Description
-----------------------------	-----------------	-------------

AQD EU ID: SEP001

AQD EU description:

Company EU Description: Heater Treater

Company EU ID: HT1

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Separator/Treater

Operating Temperature (F): 127 Operating Pressure (psig): 47.00

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre- Efficiency		Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	

Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant Pre-		Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant		Pre-	Efficiency Standards		Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards arè listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

^{**} AQD Calculated - See 'Help' for more information.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

Not Affected

Required Public Document Attachment Type Id	Description
---	-------------

AQD EU ID: SEP002

AQD EU description:

Company EU ID: SEP1

Company EU Description: unheated 3-phase

HP separator

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Separator/Treater

Operating Temperature (F): 83 Operating Pressure (psig): 653.00

Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	Basis for	
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*	
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0		
PM # 10 microns in diameter (PE/PM10)	0	0		0	0		
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0		
Sulfur dioxide (SO2)	0	0		0	0		
Nitrogen oxides (NOx)	0	0		0	0		

Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant		Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

ſ	Pollutant	Pollutant Category Co	Pre-	Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards arè listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 61) National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

^{**} AQD Calculated - See 'Help' for more information.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

Not Affected

AQD EU ID: TNK001

AQD EU description:
Company EU ID: T1

Company EU Description: 400-bbl oil

storage tank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

- Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 15.8000 Units: barrels/hr

:

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 4.00

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

	1	I	I		T	T
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	
Volatile organic compounds (VOC)	41.8	0		0.19	0.8	Tanks Program
Lead (Pb)	0	0		0	0	
Total Hazardous Air Pollutants (HAPs)	2.7	0		0.01	0.05	Tanks Program
Fluoride (F)	0	0		0	0	
Hydrogen Sulfide (H2S)	0	0		0	0	
Mercury (Hg)	0	0		0	0	
Total Reduced Sulfur (TRS)	0	0		0	0	
Sulfuric Acid Mist (SAM)	0	0		0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

- Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

- Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary

Subject to subpart

CFR 60 - Standards of Performance for New Stationary Sources.

NSPS Subpart									
0000 -	Crude	Oil	and	Natural	Gas	Production,	Transmission	and	Distribution

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	iu		

AQD EU ID: TNK002

AQD EU description:
Company EU ID: T2

Company EU Description: 400-bbl oil

storage tank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

- Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 15.8000 Units: barrels/hr

:

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 4.00

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

	1	I	I		T	T
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	
Volatile organic compounds (VOC)	41.8	0		0.19	0.8	Tanks Program
Lead (Pb)	0	0		0	0	
Total Hazardous Air Pollutants (HAPs)	2.7	0		0.01	0.05	Tanks Program
Fluoride (F)	0	0		0	0	
Hydrogen Sulfide (H2S)	0	0		0	0	
Mercury (Hg)	0	0		0	0	
Total Reduced Sulfur (TRS)	0	0		0	0	
Sulfuric Acid Mist (SAM)	0	0		0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary

Sources.

Subject to subpart

NSPS Subpart									
0000 -	Crude	Oil	and	Natural	Gas	Production,	Transmission	and	Distribution

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	l Id		

AQD EU ID: TNK003

AQD EU description:
Company EU ID: T3

Company EU Description: 400-bbl oil

storage tank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 15.8000 Units: barrels/hr

:

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 4.00

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0	
Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	41.8	0	0.19	0.8	Tanks Program
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	2.7	0	0.01	0.05	Tanks Program
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary

Subject to subpart

Sources.

NSPS Subpart									
0000 -	Crude	Oil	and	Natural	Gas	Production,	Transmission	and	Distribution

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	iu		

AQD EU ID: TNK004

AQD EU description:
Company EU ID: T4

Company EU Description: 400-bbl oil

storage tank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 15.8000 Units: barrels/hr

:

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 4.00

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

	1	I	I		T	T
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	
Nitrogen oxides (NOx)	0	0		0	0	
Carbon monoxide (CO)	0	0		0	0	
Volatile organic compounds (VOC)	41.8	0		0.19	0.8	Tanks Program
Lead (Pb)	0	0		0	0	
Total Hazardous Air Pollutants (HAPs)	2.7	0		0.01	0.05	Tanks Program
Fluoride (F)	0	0		0	0	
Hydrogen Sulfide (H2S)	0	0		0	0	
Mercury (Hg)	0	0		0	0	
Total Reduced Sulfur (TRS)	0	0		0	0	
Sulfuric Acid Mist (SAM)	0	0		0	0	

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Subject to subpart

	NSPS Subpart								
0000 -	Crude	Oil	and	Natural	Gas	Production,	Transmission	and	Distribution

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	iu		

AQD EU ID: TNK005

AQD EU description:
Company EU ID: T5

Company EU Description: 400-bbl produced

water storage tank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 0.8000 Units: barrels/hr

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 0.01

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0
Sulfur dioxide (SO2)	0	0	0	0
Nitrogen oxides (NOx)	0	0	0	0
Carbon monoxide (CO)	0	0	0	0
Volatile organic compounds (VOC)	0	0	0	0
Lead (Pb)	0	0	0	0
Total Hazardous Air Pollutants (HAPs)	0	0	0	0
Fluoride (F)	0	0	0	0
Hydrogen Sulfide (H2S)	0	0	0	0
Mercury (Hg)	0	0	0	0
Total Reduced Sulfur (TRS)	0	0	0	0
Sulfuric Acid Mist (SAM)	0	0	0	0

Pollutant	Pollutant	Pre- Efficiency Standard		Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS) New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Subject to subpart

NSPS Subpart									
0000 -	Crude	Oil	and	Natural	Gas	Production,	Transmission	and	Distribution

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)

Not Affected

These rules are found under WAQSR Chapter 6, Section 4.

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section 13.

Required Attachment	Public Document	Attachment Type	Description
Attachinent	iu		

AQD EU ID: TNK006

AQD EU description:
Company EU ID: T6

Company EU Description: 400-bbl emergency

cank

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Storage Tank/Silo

Maximum Hourly Throughput 0.0000 Units: barrels/hr

Is Tank Heated: No

Operating Pressure (psig): 0.01 Vapor Pressure of Material 0.01

Stored (psig):

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	_ Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	

PM # 2.5 microns in diameter (PE/PM2.5)	0	0	0	0	
Sulfur dioxide (SO2)	0	0	0	0	
Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	 0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

Pollutant	Pollutant	Pre- Efficiency Standard		Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency	Standards	Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		(lbs/hr)*	(tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards are listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

^{**} AQD Calculated - See 'Help' for more information.

National Emission Standards for Hazardous Air

Pollutants (NESHAP Part 63)
National Emission Standards for Hazardous Air Pollutants

(NESHAP Part 63) standards are listed under 40 CFR 63.

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Not affected

Non-Attainment New Source Review

Not Affected

These rules are found under WAQSR Chapter 6, Section

Required Pub Attachment	ıblic Document Id	Attachment Type	Description
----------------------------	----------------------	-----------------	-------------

AQD EU ID: VNT001

AQD EU description:

Company EU ID: VRT1

Company EU Description: Vapor Recovery

Tower

Source Installation or Modification Schedule – Select reason(s) for this emissions unit being included in this application (must be completed regardless of date of installation or modification):

Construction(greenfield/new facility)

Date production began:

03/01/2015

Emission Unit Type Specific Information

Emission Unit Type: Process Vent

Flow Rate or Throughput: 2654.4 Units: gallons/hr

VOC Concentration (%): 95.000 HAPs Concentration (%): 6.400

- Potential Operating Schedule - Provide the operating schedule for this emissions unit

Hours/day: 24 Hours/year: 8760

Emissions Information "Potential to emit" means the maximum capacity of a source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation is enforceable by the EPA and the Division. This term does not alter or affect the use of this term for any other purposes under the Act, or the term "capacity factor" as used in Title IV of the Act or the regulations promulgated thereunder.

Basis for Determination Options:

- Manufacturer Data
- Test results for this source
- Similar source test results
- GRICalc
- Tanks Program
- AP-42
- Other. If this is selected, attach a document with a description of the method used.

Pollutant	Pre-	Efficiency	Standards	Potential to	Potential to	Basis for
	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (Ibs/hr)*	Emit (PTE) (tons/yr)*	Determinatio n*
Particulate emissions (PE/PM) (formerly particulate matter, PM)	0	0		0	0	
PM # 10 microns in diameter (PE/PM10)	0	0		0	0	
PM # 2.5 microns in diameter (PE/PM2.5)	0	0		0	0	
Sulfur dioxide (SO2)	0	0		0	0	

Nitrogen oxides (NOx)	0	0	0	0	
Carbon monoxide (CO)	0	0	0	0	
Volatile organic compounds (VOC)	0	0	0	0	
Lead (Pb)	0	0	0	0	
Total Hazardous Air Pollutants (HAPs)	0	0	0	0	
Fluoride (F)	0	0	0	0	
Hydrogen Sulfide (H2S)	0	0	0	0	
Mercury (Hg)	0	0	0	0	
Total Reduced Sulfur (TRS)	0	0	0	0	
Sulfuric Acid Mist (SAM)	0	0	0	0	

ſ	Pollutant	Pollutant		Efficiency	Standards	Potential to		
		Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*	Units*	Emit (PTE) (lbs/hr)*	(tons/yr)*	Determinati on*

Greenhouse Gases (GHGs):

Pollutant	Pollutant	Pre-	Efficiency Standards		Potential to		
	Category	Controlled Potential Emissions (tons/yr)	Potential to Emit (PTE)*		Emit (PTE) (lbs/hr)*	Emit (PTE) (tons/yr)*	Determinati on*

^{*} Provide your calculations as an attachment and explain how all process variables and emissions factors were selected. Note the emission factor(s) employed and document origin. Example: AP-42, Table 4.4-3 (8/97); stack test, Method 5, 4/96; mass balance based on MSDS; etc.

Best Available Control Technology (BACT)

Was a BACT Analysis completed for this unit? No

Lowest Achievable Emission Rate (LAER)

Was a LAER Analysis completed for this unit? No

Federal and State Rule Applicability

New Source Performance Standards (NSPS)

New Source Performance Standards arè listed under 40 CFR 60 - Standards of Performance for New Stationary Sources.

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 61)

National Emissions Standards for Hazardous Air Pollutants (NESHAP Part 61) are listed under 40 CFR 61. (These include asbestos, benzene, beryllium, mercury, and vinyl chloride).

Not affected

National Emission Standards for Hazardous Air Pollutants (NESHAP Part 63)

National Emission Standards for Hazardous Air Pollutants

^{**} AQD Calculated - See 'Help' for more information.

(NESHAP Part 63) standards are listed under 40 CFR 63.

Not Affected

Prevention of Significant Deterioration (PSD)These rules are found under WAQSR Chapter 6, Section 4.

Not Affected

Non-Attainment New Source Review
These rules are found under WAQSR Chapter 6, Section 13.

Required Public Document Id	nt Attachment Type	Description
-----------------------------	--------------------	-------------